

ECORAIN 1" (25mm) CELL SPECIFICATION SHEET



ET-1301

	Standard Used	Metric	Imperial
Width		500mm	1.64'
Length		600mm	1.97'
Height		25mm	1"
Area		0.300076 m ²	3.23 ft ²
Void Surface Area		80% .23 cubic feet	80%
Material		100% Recycled Polypropylene	
Biological & Chemical Resistance		Material is unaffected by moulds and algae, soil-borne chemicals, bacteria and bitumen.	
Service Temperature		-30°C to 120°C	-22°F to 248°F
Compressive Strength/ Ultimate Load	ASTM D1621	±205.56 t/m ²	±306.80 psi
Flow Rate per Unit Width	ASTM D4716	>120 lt/min	>31.70 gal/min

NOTE: ALL ECORAIN PRODUCTS & SYSTEMS ARE WORLDWIDE PATENT PENDING & DESIGN REGISTERED.

Disclaimer: All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. This information is intended only as a general guide, no responsibility can be accepted for any errors, omissions, or incorrect assumptions. As each project is unique, and as EcoRain Tank Systems and its distributors and agents worldwide have no direct control over the methods employed by the user in specifying, installing, or supervising of its products hence Eco-Rain Systems and its distributors and agents worldwide accept no responsibility. Users should satisfy themselves as to the suitability of the product for their purpose. All product designs and specifications are subject to change without further notice.



EcoRain Tank Systems of America, Inc.

contact@ecoraintank.com +1.818.501.0424 www.ecoraintank.com